


# MODEL 4J SERIES – FRAME Size II

## LATCH NEEDLE SINKER TOP, SINGLE KNIT MACHINE

### Four Track Fabric Patterning

Available in 6 Interchangeable Diameters



### option features

- Preset revolution counter
- Lycra feed system
- Omnidirectional warning light system – 2 color
- Lock-out switch – manual motor starting switch setup for manual lockout
- Standard range of voltages available (380, 416, 480, 550 VAC)
- Upper level multi-directional single fan lint blowing system
- Multi-positive storage feeding system



**TOMPKINS USA**

623 Oneida Street  
 Syracuse, New York U.S.A. 13202  
 Telephone: (315) 422-8763  
 FAX: (315) 422-8762  
 Website: [www.tompkinsusa.com](http://www.tompkinsusa.com)  
 Email: [customerservice@tompkinsusa.com](mailto:customerservice@tompkinsusa.com)

### Specifications

Diameter	Model No.	Feeds	RPM*	Cut
11 inch (27.94cm)	4J1144	44	100	16-28
12 inch (30.48cm)	4J1248	48	92	16-28
13 inch (33.02cm)	4J1352	52	85	16-28
14 inch (35.56cm)	4J1456	56	79	16-28
15 inch (38.10cm)	4J1560	60	73	16-28
16 inch (40.64cm)	4J1664	64	69	16-28

\*Machine RPM is dependent on yarn quality and fabric configuration.

### Machine Specifications

Height	105 in. (266.70 cm) to the top of Side Creel Tubes
Width – Outside Diameter At Positive Storage Feeders	60 in. (152.4 cm)
At Floor	37 in. x 38 in. (94.0 cm x 96.5 cm)
Weight	1700 pounds (771 kg)
Horsepower	2.0
Drive System	Tompkins Electronic AC Motor Controller with smooth and quiet Eagle Cogbelt Drive
Standard Electrics	All models 220 volts, single or 3 phase, 50/60 hertz power (voltage range 253 to 188). If other operating voltage is required, contact Tompkins.
Track	Four track
Positive Storage Feeder System	With input and output stop motions, tensioner and knot catcher – standard on all models.
Fabric Collection – Electronic	2 roll balanced takedown system to reduce high speed vibration with precision rollup for 24 inch diameter roll.
Interchangeable Heads Rapid Change System	All diameters in the Frame Size II range of 11 to 16 inches. For Example: The knitting head of a 11 inch diameter machine can be easily replaced with a 16 inch diameter knitting head.
Drop gates	For easy accessibility.
Machine Speeds	Start, stop and jog, with three programmable jog speeds.
Needle Detectors	Standard on all models
Lubrication System	Projectile lubricator with auto flush system.
Safety Roll Shutoff	Standard on all models

### Creel Specifications

Side Creel	unlimited yarn cone capacity. Complete with hard tubes, support brackets and all hardware setup for double coning. Ceramic guides at all yarn bends and entrances.
------------	--