

TOMPKINS SRM LLC

MODEL KDK SERIES KNITTING MACHINE

Dual Heads with Individual Motor Control



TOMPKINS USA

**THE SMALL DIAMETER & BODY SIZE
CIRCULAR KNITTING MACHINE SPECIALIST**

623 Oneida Street Syracuse, New York 13202
Tel: (315) 422-8763 Fax: (315) 422-8762
customerservice@tompkinsusa.com

TOMPKINS is a registered trademark of Tompkins USA

Website: www.tompkinsusa.com

Machine Specifications

Diameter: 4 inch* (10.16 cm)

Cut (needles/inch): 16-32*

No. Feeds/Knitting Head: 1

RPM: 700-1100**

**Contact Tompkins about other sizes and cuts*

***Machine RPM is dependent on yarn quality and fabric configuration.*

Dimensions	24 in. depth x 28 in. width x 44 in. height (Top of bed plate)
	24 in. depth x 28 in. width x 92 in. height (over all)

Weight	750 pounds
---------------	------------

Horsepower	1/4 per head
-------------------	--------------

Drive System	Tompkins SRM Electronic AC Motor Controller
---------------------	--

Standard Electrics	All models 220 volts, single or 3 phase, 50/60 hertz power (voltage range 253 to 188). If other operating voltage is required, contact Tompkins SRM.
---------------------------	---

Fabric Collection	2 roll takedown and roll up system
--------------------------	------------------------------------

Feeder System	Electronic Tension Feeder by BTSR .1-50 gram programmable
----------------------	--

Safety Roll Shutoff	Standard on all models
----------------------------	------------------------

Lubrication System	Adjustable flow control for each knitting head. In line solenoid used to shut flow off when machine is stopped.
---------------------------	---

Creel	Standard four cone, machine supported – optional floor standing
--------------	--

Applications	Knit-de-knit, medical, filter, food processing and industrial
---------------------	--